


423



Full- or Part-Circle Metal Impact Sprinkler

Primary applications: 1/2" Riser-mounted for residential and small public areas, also on spike or sled bases


- All-metal construction provides years of trouble-free use.
- User-friendly, fingertip adjustment to full- or part-circle mechanism.
- Anti side-splash arm prevents wasteful side-splash onto buildings and walkways.
- Deflector shield and diffuser screw control distance and stream pattern.
- Colour-coded nozzle inserts

Spacing between sprinklers: up to 14.0 m (45 ft)
 Pressure: 1.5 to 4.0 bar (20 to 55 psi)
 1/2" Male pipe connection
 Weight: 270 gr.

423			
Nozzle mm	P bar	Q m ³ /h	D m
3.2 Green	1.5	0.50	22
	2.0	0.57	23
	3.0	0.70	25
	4.0	0.81	26
3.5 Blue	1.5	0.58	23
	2.0	0.66	24
	3.0	0.81	26
	4.0	0.93	27
4.0*	1.5	0.73	23
Black	2.0	0.85	25
	3.0	1.03	27
	4.0	1.18	28

* Standard Nozzle

421



Full-Circle Metal Impact Sprinkler

Primary applications: 1/2" Riser-mounted for residential and small public areas

- All-metal construction provides years of trouble-free use.
- Diffuser screw controls distance and stream pattern.
- Colour-coded nozzle inserts

Spacing between sprinklers: up to 14.0 m (45 ft)
 Pressure: 1.5 to 4.0 bar (20 to 55 psi)
 1/2" Male pipe connection
 Weight: 195 gr.

421			
Nozzle mm	P bar	Q m ³ /h	D m
3.2 Green	1.5	0.50	22
	2.0	0.57	23
	3.0	0.70	25
	4.0	0.81	26
3.5 Blue	1.5	0.58	23
	2.0	0.66	24
	3.0	0.81	26
	4.0	0.93	27
4.0*	1.5	0.73	23
Black	2.0	0.85	25
	3.0	1.03	27
	4.0	1.18	28

* Standard Nozzle

