

525/2 Pop-up

Gear-Driven Pop-up

Primary applications: Residential lawns

Main features

- Gear-driven design for quiet operation
- Water-lubricated for reliable rotation and durability
- Easy to set full- or part-circle fingertip adjustment
- Stream distance adjustment deflector
- Colour-coded adjustable parts for easy identification
- Removable filter screen for easy maintenance
- Built in anti-drainage valve, holds 5.0 m elevation
- Ribbed canister provides anti-vandalism anchoring

Technical data

Spacing between sprinklers: up to 12.0 m

Pressure: 2.0 - 4.0 bar

1/2" Female water inlet



Performance table

Nozzle mm	P bar	Q m ³ /h	D m
3.0	2.0	0.51	20.0
Orange	3.0	0.63	21.0
	4.0	0.72	22.0
3.2	2.0	0.57	20.0
Green	3.0	0.70	21.5
	4.0	0.81	22.0
4.0*	2.0	0.85	21.0
Red	3.0	1.03	22.0
	4.0	1.18	23.0

* Standard nozzle

805 Pop-up

Impact Sprinkler

Primary applications: Residential and public lawns

Main features

- Reliable impact plastic head for underground installation
- Full- or part-circle pattern adjustment.
- Diffuser screw breaks water into smaller droplets for uniform watering
- Extra high 7.60 cm pop-up clearance
- Rugged ribbing case for maximum strength and durability, also provides anti-vandalism anchorage
- Sand-proof seals and removable filter screen for easy maintenance
- Colour-coded nozzles

Technical data

Spacing between sprinklers: up to 12.0 m

Pressure: 2.0 - 4.0 bar

1/2" Female water inlet



Performance table

Nozzle mm	P bar	Q m ³ /h	D m
2.8	2.0	0.45	21
Orange	3.0	0.55	23
	4.0	0.63	23
3.0	2.0	0.51	22
Red	3.0	0.63	24
	4.0	0.72	25
3.2	2.0	0.57	23
Green	3.0	0.70	24
	4.0	0.81	25
3.5	2.0	0.66	23
Blue	3.0	0.81	24
	4.0	0.93	26
4.0*	2.0	0.85	24
Black	3.0	1.03	25
	4.0	1.18	26

* Standard nozzle